



- ◇ Fast switching devices
- ◇ Low Reverse Leakage Current
- ◇ ROHS Compliant
- ◇ UL-94 V-0 / Green EMC
- ◇ Matte Tin Lead finish (Pb-Free)

Device Marking Code	
BAS16L	S2

Pin & Polarity



Maximum Ratings (Ta = 25 °C)


Symbol	Parameter	Value	Units
V_{RSM}	Non-Repetitive Peak Reverse Voltage	100	V
V_{RRM}	Peak Repetitive Reverse Voltage	75	V
V_{RWM}	Working Peak Reverse Voltage		
V_R	Dc Blocking Voltage		
I_{FRM}	Repetitive Peak Forward Current	300	mA
I_O	Average Forward Current	100	mA
I_{FSM}	Non-Repetitive Peak Forward Current*1	2	A
P_D	Power Dissipation	200	mW
T_J	Junction Temperature	150	°C
T_{STG}	Storage Temperature	-55 to +150	°C

Electrical Characteristics (Ta = 25 °C unless otherwise noted)


Symbol	Parameter	Conditions	Min	Typ	Max	Units
V_R	Reverse Voltage	$I_R=100\mu A$	75			V
V_F	Forward Voltage	$I_F=5mA$	0.62		0.72	V
		$I_F=10mA$			0.855	
		$I_F=100mA$			1.0	
		$I_F=150mA$			1.25	
I_R	Reverse Leakage Current	$V_R=80V$			100	nA
		$V_R=20V$			25	
C	Capacitance	$V_R = 0.5V, f = 1MHz$			3	pF
T_{RR}	Reverse Recovery Time	$I_F = I_R = 10mA$ $I_{RR} = 1mA, R_L = 100\Omega$			4	ns

*1: Pulse width = 1 μ s


RATING AND CHARACTERISTICS CURVES (BAS16L)




Forward current (I_F) vs Forward voltage (V_F)



Reverse current (I_R) vs Reverse voltage (V_R)



Power Derating Curve




Capacitance vs Reverse voltage (V_R)

ORDERING INFORMATION

Device	Package	Shipping	Tape wide	Emboss pitch	Tape specification	Package Code
BAS16L	DFN1006-2L	Tape & Reel 10000pcs /7" Reel	8mm	4mm	Conductive	-T

Package Dimensions



DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.